

AJ 9300 - IX
COVER and AUTO JIG AUTOMAT



HEAD OFFICE

Basin Expres Yolu Mehmet Akif Mah. Bahariye Cad. No:105
34303 K.Çekmece / İSTANBUL / TURKEY
Tel: +90 212 472 01 01
Fax: +90 212 612 79 65

FACTORY

Konya Ankara Yolu. Havaalanı Kavşağı
No: 213
42100 Selçuklu / KONYA
Tel: +90 332 358 01 01
Fax: +90 332 358 09 00




AJ 9300 - IX

COVER and AUTO JIG AUTOMAT



AJ 9300 - IX




AJ 9300 - IX




AJ 9300 - IX




AJ 9300 - IX




model 1




model 2




model 3




model 4




model 5



model 6



model 7



model 8

AJ 9300 - IX

COVER and AUTO JIG AUTOMAT

Automatic sewing unit AJ 9300 – IX for run-stitching and cutting small parts in one step. For simultaneous run-stitching and trimming small parts such as flaps, waistband extensions, shoulder flaps, cuffs etc.

TECHNICAL SPECIFICATIONS

Brother Direct Drive Sewing Head
Beijer Electronics, Windows Based 256 Million Colour Supported Touch Screen Control Panel
Easy to use, with Pictures on the Operator Panel and with 50 Different Programming
Sequential/Cycle Programming for Different jig Models
PLC Control Unit
Automatic Cycling Step Motor Unit to move the Jig
Program support enabling Easy and Comfortable Jacket Flaps of Different Patterns
Program supports easy and Comfortable working options for round, angled and Square Latch Ends for Trousers
Possibility of programming for corner-stitches of Jigs and adjusting stitch steps
Programmable start and end back tack or optionally adjustable stitch condensing
Automatic thread trimming and cleaning system at the end of sewing
Linear Motor Control, Edge Cutting System
Ability to fix the Jig length (stitch) from panel either with photocell or mm
Ability to make front and end cutting in stitch start and end, stitch side cuts
Ability cutting- width (after sewing edge) between 3.3mm and 6 mm
Suction Unit for Cutting waste with waste Collection Chamber
Jig Ejection upon finish
Error Detecting Systems
Thread monitor

AREAS OF USAGE

Man Jacket and Woman Jacket Side Pocket Flaps
Man Trousers and Women Trousers Latch Ends and Flaps
Coat, Topcoat Side Pocket Flaps and Shoulder Straps
Various parts of Military Camouflage Patterned Cloth

PERFORMANCE

3.500 - 4.000 Pieces Sewing Patterns

DIMENSIONS

Lenght : 115 cm

Width : 80 cm

Height : 112 cm

Packing Size : 127 cm x 89 cm x 145 cm

Machine Net Weight : approx. 135 kg

Machine Gross Weight : approx. 155 kg

Max. Sewing Speeds : 3.600 r.p.m

Max. Stitch Length : 0,5 or 5 mm

Connection Voltage: Single-Phase A.C. 230 V, 50/60 Hz

Air Pressure : 6 bar