

KL 3100-EXT

PRE-GATHERING OF SLEEVES AND THE TAPING OF ARMHOLES



HEAD OFFICE

Basin Expres Yolu Mehmet Akif Mah. Bahariye Cad. No:105
34303 K.Çekmece / İSTANBUL / TURKEY
Tel: +90 212 472 01 01
Fax: +90 212 612 79 65


FACTORY

Konya Ankara Yolu. Havaalanı Kavşağı
No: 213
42100 Selçuklu / KONYA
Tel: +90 332 358 01 01
Fax: +90 332 358 09 00



KL 3100-EXT

PRE-GATHERING OF SLEEVES AND THE TAPING OF ARMHOLES



KL 3100-EXT



KL 3100-EXT



KL 3100-EXT



KL 3100-EXT

Max. Sewing Speeds : 5.000 r.p.m
 Max. Stitch Length : 0,5 or 5 mm
 Stitch type : 301 (Lockstitch)

Connection Voltage:
 Single-Phase A.C. 230 V, 50/60 Hz

Air Pressure : 6 bar

KL 3100-EXT

PRE-GATHERING OF SLEEVES AND THE TAPING OF ARMHOLES

KL 3100-EXT the pre-gathering of sleeves and the taping of armholes provide the basis for an ideal fit of the sleeve.
 For these requirements the KL 3100-EXT provides a fully developed workplace which is precisely adjusted to the necessary working processes and quality demands and therefore serves as an important manufacturing resource for the work step `pre-gathering sleeves and bridle-taping armholes`

TECHNICAL SPECIFICATIONS

Pegasus EXT 3216 Series or Juki MO-8900 Five thread overlook head with Differential top- and bottom feed
 Short table, Machine frame with adjustable height providing the possibility of working from the front
 Beijer Electronics, Windows Based 256 Million Colour Supported Touch screen Control Panel
 Easy to use, with Pictures on the Operator Panel and with 50 Different Programming
 Sequential / Cycle Programming for Different arm Models
 PLC Control Unit
 Efka 550 W Mini Stop DC Servo Sewing Motor
 Automatic tape loading System for guiding the tape under the feed
 Automatic tape Cutting at sewing end
 Automatic Start with Photocell or Pedal control
 Automatic Thread Cutting and Cleaning System at the end of sewing
 Air controlled zippy unit for perfect side stitching
 Air blowing system on table top to Relaxing workflow
 Graphical program enabling bottom and top fullness at desired zones on work
 Step Motor Controlled fullness Unit for automatic top fullness operation
 Step Motor Controlled fullness Unit for automatic bottom fullness operation
 Yarn waste compartment

OPTIONS

Universal Stacking

PERFORMANCE

Jacket:

Pre-ruffling of the arm crown with or without sleeve head. Taping of the armholes.

Sewing Style Chain Stitch

Length from 11 mm to 5 mm

Stitch Speed 1.000-5.000 Rpm

DIMENSIONS

Length : 115 cm

Width : 85 cm

Height : 110 cm

Packing Size : 127 cm x 89 cm x 145 cm

Machine Net Weight : approx. 130 kg

Machine Gross Weight : approx. 150 kg